SUBJECT INDEX

Activation energy, p. 207
Amine treatment, p. 282
Antistrip additives, p. 282
Aramids, p. 45
Ashland Process, p. 11
Asphalt-aggregate systems, p. 282
Asphalt concrete, p. 282
Blend morphology, p. 230
Blends, p. 133
Bonding agents, p. 103
Burst factor, p. 28
Carbon black, p. 308
Chlorosulfonated polyethylene, p. 340
Compatibilizer, p. 133
Core-box process, p. 328
Core-making process, p. 11
Corrosion inhibitive polymers, p. 68
Corrosion inhibitors, p. 68
Corrosion rate measurement, p. 68
Cross-linking, pp. 118, 230
Cure characteristics, p. 230
Curing behavior, p. 308
Darcy's law, p. 11
Dicumyl peroxide, p. 230
Die swell, p. 340
Dynamic shear rheometry, p. 245
Dynamic vulcanization, p. 133
Elasticity, p. 328
Embrittlement, p. 55
Emulsion, p. 207
Emulsion lattices, p. 28
Epoxy, p. 197
ESEM, p. 282
Extraction resistant, p. 55
Fibers, pp. 45, 103, 118
Filler dispersion, p. 308
Fluidized bed, p. 11
Fluorescence microscopy, p. 245
Friction factor, p. 11
HALS hindered amine stabilizer, p. 55
High pressure capillary viscometer, p. 340
High temperature stretching, p. 230
Hydrostatic pressure testing, p. 55
Interfacial bonding, p. 103
Internal mixer, p. 133
IR, p. 197
Kevlar, p. 45
Lime treatment, p. 282
Long-term thermal stability, p. 55
Mechanical properties, pp. 45, 133, 308
Melt fracture, p. 340
Microfibril, p. 118
Moisture damage, p. 282
Morphology, p. 133
Negative deviating blends, p. 340
NMR, p. 197
Non-Newtonian, p. 328
Normal stresses, p. 328
Oxidation induction time, p. 55
Oxidation polymerization, p. 68
Palm oil fatty acid additive, p. 308
Phenolic-urethane, p. 328
Phenolic-urethane-amine, p. 11
Plasma, p. 118
  polyamides, p. 45
  polyamines, p. 68
  polyanilines, pp. 68, 197
  polyester, p. 45
  polymer blends, p. 230
  polymer modifiers, p. 245
  polymeric substance, pp. 28, 207
  polymerization, pp. 45, 207
  polyolefin, pp. 55, 230
  polypropylene, pp. 45, 133
  polyurethane elastomer, p. 103
  porous media, p. 11
Positive deviating blends, p. 340
Positive-negative deviating blends, p. 340
Relaxation time, p. 328

Retained polymer, p. 28
Reynold's number, p. 11
Rheology, pp. 11, 133, 245, 328, 340
Room temperature stretching, p. 230
Rubber, pp. 133, 230, 340
  bromobutyl, p. 230
  carboxylated nitrile, p. 340
  devulcanized, p. 133
Sand-binder, p. 11
SBR treatment, p. 282
Sealants, p. 161
Self-vulcanizable blends, p. 340
Short fiber composite, p. 103
Spectrophotometric measurements, p. 68
Steel protection, p. 68
Stress relaxation, p. 103
Styrene, p. 207
Sulfur cure, p. 230
Surface treatment, p. 118
Surfactant, p. 207
Synthetic, p. 45
Tear factor, p. 28
Telechelic, p. 197
Thermal properties, p. 133
Thermal treatment, p. 28
Thermoset, p. 197
Tire rubber, p. 133
Twin screw extruder, p. 133
UHMPG fibers, p. 118
Vinyl acetate, p. 207
Viscosity, p. 328
Water absorption, p. 28
Water-borne, p. 197
Water-gas pipe, p. 55

AUTHOR INDEX

Abd El-Ghaffar, M. A., p. 68
Abd El-Hakim, A. A., p. 28
Andreopoulos, A. G., p. 118
Ayoub, M. M. H., p. 207
Badran, A. S., p. 28
Bakhtiyarov, S. I., pp. 11, 328
Darwish, W. M., p. 68
Das, C. K., p. 230
Dörner, G., p. 55
Feng, Q., p. 197
Francis, J., p. 296
Gupta, B. R., p. 340
Helaly, F. M., p. 68
Isayev, A. I., p. 133
Ismail, H., p. 308
Janssen, D. J., p. 161
Kramer, E., p. 55
Kumar, S., p. 45
Kutty, S. K. N., p. 103
Luo, T., p. 133
Lynch, L. N., p. 161
Maret, J., p. 296
Mathew, N. M., p. 296
Miknis, F. P., p. 282
Mohamed, E. S., p. 28
Mukhopadhyay, S., p. 340
Nada, A. M. A., p. 28
Nando, G. B., p. 103
Newman, J. K., p. 245
Ng, C. T., p. 308
Overfelt, R. A., pp. 11, 328
Patra, P. K., p. 230
Polk, M. B., p. 45
Sahayadasan, J., p. 296
Schmutz, T., p. 55
Suhara, F., p. 103
Tarantili, P. A., p. 118
Toland, A., p. 197
Viswanathan, T., p. 197
Williams, T. M., p. 282
Youssef, E. A. M., p. 68
Zweifel, H., p. 55